WT-26 Rewind System



910 BOLGER COURT. FENTON, MO 63026 . USA (800) 325-9777 (636) 343-0806 FAX: (636) 343-6629 sales@webtechniquesinc.com | webtechniquesinc.com



WT-26 Shown

SOLVE YOUR LABEL INVENTORY ISSUES WITH A WEB TECHNIQUES REWIND SYSTEM

SAVE MONEY AND TIME BY QUICKLY AND ACCURATELY COUNTING AND REWINDING YOUR LABELS WITH A WEB TECHNIQUES REWIND SYSTEM.

- 1. FAST, EASY TO USE
- 2. REQUIRES PRACTICALLY NO SET-UP TIME
- 3. QUICKLY REWINDS LARGE MASTER ROLLS INTO ROLLS OF PREDETERMINED COUNT

FEATURES:

1. INFINITELY VARIABLE MOTOR SPEED CONTROL

System will automatically "over speed" the motor, rewinding smaller diameter cores twice as fast as the WT-25 rewind system family

2. HIGH VISIBILITY, BACKLIT TOUCH SCREEN CONTROL

Dual Preset: Set one point for deceleration and a second point for final stop Counts in both English or Metric Units at the touch of a button

- 3. WIND LABELS IN OR OUT
- 4. STAINLESS STEEL REWIND SURFACE
- 5. STANDARD 10", 12" COUNTS OR METRIC INCREMENTS, COUNT INCREMENT ADJUSTABLE FROM 0.1" 99"
 MEASUREMENTS
- 6. CHOICE OF COREHOLDER STYLES

Lift-Off Cam-Lock (Mechanical)
Lift-Off Air Inflatable (Great choice for quickly switching between coreholder sizes)
Flange Mounted Air Inflatable

7. CHOICE OF COREHOLDER SIZES

Coreholders range in size from coreless to 0.4" through 6" (25mm through 120mm), Please do not hesitate to contact us with any special requests

8. CHOICE OF COUNTING SYSTEMS

Our systems are compatible with almost any counting system available, Please do not hesitate to contact us with any special requests

- (OPTIONAL) COMPRESSED AIR MODULE
 Allows WT-26 system to be operated in locations with no compressed air availability
- 10. (OPTIONAL) **SURGE PROTECTION/BATTERY BACK-UP**Protects system from power issues
- 11. (OPTIONAL) **RAZOR BLADE SLITTING ATTACHMENT**Requires air coreholder on the rewind for multiple cores
- 12. (OPTIONAL) **ERGO-LIFT HEIGHT ADJUSTMENT SYSTEM**
- 13. (OPTIONAL) **STATIC ELIMINATION SYSTEM** (DE-IONIZING SYSTEM)
- 14. (OPTIONAL) HOODED ENCLOSURE

